

# Package: scribblr (via r-universe)

August 26, 2024

**Title** A Notepad Inside RStudio

**Version** 0.2.1

**Description** A project aware notepad inside RStudio, for taking quick project-related notes without distractions. RStudio addin.

**License** GPL (>= 3)

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.1.1

**Imports** shiny (>= 0.13), miniUI (>= 0.1.1), shinyjs, rstudioapi (>= 0.5), fs, usethis, keys, gh, shinyWidgets, utils, rlang

**BugReports** <https://github.com/vgherard/scribblr/issues>

**URL** <https://vgherard.github.io/scribblr/>,  
<https://github.com/vgherard/scribblr>

**Suggests** covr, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**Repository** <https://vgherard.r-universe.dev>

**RemoteUrl** <https://github.com/vgherard/scribblr>

**RemoteRef** HEAD

**RemoteSha** daf796f325d7bf53c8eea494c1c1e3681611949c

## Contents

scribble . . . . .	2
scribblr_delete . . . . .	3
scribblr_list . . . . .	3

<b>Index</b>	<b>5</b>
--------------	----------

---

`scribble`*Open scribblr note editor*

---

**Description**

Opens the scribblr note editor in a new window.

**Usage**

```
scribble(note = NULL)
```

**Arguments**

`note` either NULL, or a length one character (not NA). See details.

**Details**

scribblr integrates a minimalist note editor within RStudio, useful for taking quick project-related notes without distractions. scribblr notes are RStudio project aware: each project has associated its own notes, which can be accessed by calling `scribble()`, and are stored into the project's root directory. Using `scribble()` without any active project will take the R home directory as root.

Calling `scribble()` with the default `note = NULL` gives access to the main project notes. Otherwise, `note` must be a string specifying a valid filename.

scribblr notes and settings for the active project are stored in the `".scribblr"` directory, under the project's root. If this, or the note specified by `note`, do not exist, the user will be prompted for permission to create the required files/directories.

Notes are autosaved when the editor is closed; until that moment, the R session will remain busy.

`scribble()` can also be called (and, in particular, associated a custom keystroke) via the RStudio Addin "Open scribblr note editor".

**Value**

returns NULL, invisibly. Called for side-effects.

**Author(s)**

Valerio Gherardi

**Examples**

```
## Not run:
scribble()

## End(Not run)
```

---

scribblr_delete	<i>Delete a scribblr note</i>
-----------------	-------------------------------

---

**Description**

Delete a scribblr note.

**Usage**

```
scribblr_delete(note)
```

**Arguments**

note	a length one character (not NA). Note to be deleted.
------	--

**Value**

returns NULL, invisibly. Used for side-effects.

**Author(s)**

Valerio Gherardi

**See Also**

[scribble](#)

**Examples**

```
## Not run:  
scribblr_delete("todo")  
  
## End(Not run)
```

---

scribblr_list	<i>List scribblr notes</i>
---------------	----------------------------

---

**Description**

List all scribblr notes.

**Usage**

```
scribblr_list()
```

**Value**

a character vector.

**Author(s)**

Valerio Gherardi

**See Also**

[scribble](#)

**Examples**

```
## Not run:  
scribblr_list("todo")  
  
## End(Not run)
```

# Index

scribble, [2](#), [3](#), [4](#)  
scribblr\_delete, [3](#)  
scribblr\_list, [3](#)